

¡Ahora en español!

The Lifeline VIEW Like You've Never **Heard** Before



The Language Softkey Icon appears on the VIEW's screen, and pressing the corresponding Softkey allows the user to toggle between **English** and **Spanish** voice instruction.

The award-winning Lifeline VIEW, the easy-to-use AED with full-motion color video, just became even more accessible. The new dual-language model allows a rescuer to choose English or Spanish as the spoken language with the simple touch of a button.



To learn more about Defibtech AEDs,
call 1-866-DEFIB-4-U or visit www.defibtech.com



Defibtech, LLC | 741 Boston Post Road, Guilford, CT 06437 USA
www.defibtech.com | 1-866-DEFIB-4U (1-866-333-4248) or 1-203-453-4507

MKT-000035 rev A
Issued: 2024-05-17

THIS DOCUMENT IS FOR USA DISTRIBUTION ONLY

Defibtech Lifeline VIEW Semi-Automatic Defibrillator

TECHNICAL SPECIFICATIONS†

DEFIBRILLATOR

TYPE

Semi-automatic external defibrillator

MODEL

DDU-2300

WAVEFORM

Biphasic Truncated Exponential
(Impedance compensated)

ENERGY

Adult: 150 Joules
Child / Infant: 50 Joules
(Nominal into 50 Ohm load)

CONTROLS

Lighted On/Off button
Lighted Shock button

CHARGE TIME*

Less than 4 seconds
(from shock advised)

DISPLAY

High-resolution color LCD

VIDEO PROMPTS

Full motion video
On-screen text prompts

CPR COACHING

Video and voice coaching
On-demand video help

VOICE PROMPTS

Extensive voice prompts guide
user through operation of the unit

RESCUE PROTOCOL

AHA/ERC (default);
supports protocol updates by
the user (password protected)

*Typical, with new battery at 25°C

DEFIBRILLATION / MONITORING PADS

MODEL

Adult: DDP-2001
Child / Infant: DDP-2002

SURFACE AREA**

Adult: 12 inches² (77 cm²)
Child / Infant:
7.75 inches² (50 cm²)

TYPE

Pre-connected, single-use,
non-polarized, disposable,
self-adhesive electrodes with
cable and connector

**Nominal, each pad

EVENT DOCUMENTATION

INTERNAL EVENT RECORD

Critical ECG segments and rescue
event parameters are recorded
(greater than 60 minutes) and
can be downloaded to a removable
data card

PC-BASED EVENT REVIEW

ECG with event tag display, and
audio playback when available

REMOVABLE STORAGE

(optional) Up to 30 hours of ECG
and event data storage (no audio
option) or up to 3 hours of audio
(audio option). ECG and event
storage on a removable data card.
Actual length of storage is
dependent on card capacity.

USB PORT

Event download and
maintenance operations

PATIENT ANALYSIS SYSTEM

PATIENT ANALYSIS

Automatically evaluates patient
impedance for proper pad contact.
Monitors signal quality and analyzes
patient ECG for shockable/
non-shockable rhythms.

SENSITIVITY/SPECIFICITY

Meets or exceeds IEC-60601-2-4
requirements; meets AAMI DF80
requirements and AHA
recommendations

BATTERY PACK

MODEL

DBP-2003 (standard),
DBP-2013 (aviation; TSO C-142a)

POWER

12V, 2800 mAh

TYPE

Lithium/Manganese Dioxide
Disposable, recyclable,
non-rechargeable

CAPACITY*

125 shocks or 8 hours
continuous operation

STANDBY LIFE*

4 years

LOW BATTERY INDICATORS

Visible
Audible

*Typical, with new battery at 25°C

SELF TESTS

AUTOMATIC

Automatic daily, weekly, monthly
and quarterly circuitry tests

BATTERY INSERTION

System integrity test on
battery insertion

PAD PRESENCE

Pads preconnected tested daily

USER-INITIATED

Unit and battery pack system
test initiated by the user

STATUS INDICATION

Visual and audible indication
of unit status

STATUS SCREEN

Unit self-test results
Pads and battery information
(status and expiration)

ENVIRONMENTAL

TEMPERATURE

Operating: 0 to 50°C (32 to 122°F)
One Hour Operating Temperature
Limit (extreme cold):
-20°C (-4°F)***
Standby: 0 to 50°C (32 to 122°F)

RELATIVE HUMIDITY

Operating / Standby: 5%-95%
(non-condensing)

ALTITUDE

-500 to 15,000 ft (-150 to 4500 m)
per MIL-STD-810F 500.4 Procedure II

VIBRATION

Ground (MIL-STD-810F 514.5
Category 20)
Helicopter (RTCA/DO-160D,
Section 8.8.2, Cat R, Zone 2,
Curve G)

Jet Aircraft (RTCA/DO-160D
Section 8, Cat H, Zone 2,
Curves B & R)

**SHOCK / DROP ABUSE
TOLERANCE**

MIL-STD-810F 516.5 Procedure IV
48 inches (1.2 meters), any edge,
corner, or surface, in standby mode

**SEALING / WATER
RESISTANCE**

IEC 60529 class IP55;
Dust Protected, Protected against
water jets (Battery pack installed)

ESD

IEC 61000-4-2: (Open air up to
15kV or direct contact up to 8kV)

EMC (Emission)

CISPR 11 Group 1 Level B
and FCC Part 15

EMC (Immunity)

IEC 61000-4-3 and IEC 61000-4-8

***From room temperature to
temperature extreme, one hour
duration, updated specification for
DDU-2000 Series AEDs running
software revision 2.4 or above

PHYSICAL

SIZE

7.3 x 9.5 x 2.3 Inches
(18.5 x 24 x 5.8 cm)

WEIGHT (with battery)

Less than 3 lbs (1.4 kg)